

# REZNOR®

## REZNOR® UNIT HEATERS BETTER THAN THE REST

Are you looking for a space-heating solution for your business, home garage or workshop? Reznor unit heaters offer the flexibility, reliability and performance you need to create a comfortable work environment. Our industry-leading unit heater design will keep your space the right temperature so you can focus on the project at hand. Check out what makes our systems better than the rest.

### FEATURES & BENEFITS

- Power vented and separated combustion options in all sizes
- High efficiency levels
- Low amp draw
- Low emission levels
- Low sound levels
- Aesthetically pleasing design
  - Two-tone black and white powder coat, scratch-resistant paint scheme
  - Clean metal panels without any visible screws and fasteners
- Models UDZ and UDX sizes 30 - 125 approved for residential use
- Variety of options
  - 409 or 316 stainless steel heat exchangers
  - 409 stainless steel burners
  - Two-stage gas valve and thermostat
- Variety of unique standard features
- TCORE® titanium stabilized heat exchanger
- "G" terminal and circuit board design allow for fan only operation
- Single burner design (regardless of capacity)
- Ease of conversion (one spring, one orifice)
- External gas connection
- Low voltage wiring connections
- Up to 93% efficiency on model UEZ



JOIN OUR LEGACY. CHOOSE REZNOR.

# REZNOR VERSES THE REST

## COMPETITIVE WARRANTY

We stand by our industry-leading unit heater. That is why we offer one of the longest warranties in the business, five years on parts and 10 years on the heat exchanger.

BRAND	UNIT HEATER CAPACITY						
	30	40	60	75	100	125	
<b>REZNOR UDX</b>	30	40	60	75	100	125	
Approved for Residential Use	✓	✓	✓	✓	✓	✓	
Full Load Amps (115 volt)	1.9	2.4	2.4	3.7	4.3	5.6	
Throw @ 10'	22	37	39	52	52	60	
Ext. 24v Wiring	✓	✓	✓	✓	✓	✓	
Single Burner	✓	✓	✓	✓	✓	✓	
External Gas	✓	✓	✓	✓	✓	✓	
Low Profile	✓	✓	✓	✓	✓	✓	
Efficiency	82	83	83	83	83	83	
<b>Competitor W's Unit</b>	30	45	60	75	100	125	
Approved for Residential Use	✓	✓	✓	✓	✓	✓	
Full Load Amps (115 volt)	3.7	3.7	2.5	2.5	4.7	4.2	
Throw @ 10'	25	27	36	38	42	56	
Ext. 24v Wiring							
Single Burner							
External Gas							
Low Profile	✓	✓	✓	✓	✓	✓	
Efficiency	80	80	80	80	80	80	
<b>Competitor X's Unit</b>	30	45	60	75	90	105	120
Approved for Residential Use	✓	✓	✓	✓	✓	✓	✓
Full Load Amps (115 volt)	3.0	3.0	4.1	4.1	6.4	6.4	6.4
Throw @ 10'	?	?	?	?	?	?	?
Ext. 24v Wiring	✓	✓	✓	✓	✓	✓	
Single Burner	✓	✓	✓	✓	✓	✓	
External Gas	✓	✓	✓	✓	✓	✓	
Low Profile	✓	✓	✓	✓	✓	✓	
Efficiency	81	81	81	81	81	81	
<b>Competitor Y's Unit</b>	30	45	60	75			
Approved for Residential Use	✓	✓	✓	✓			
Full Load Amps (115 volt)	2.7	2.7	5.1	5.1			
Throw @ 10'	?	?	?	?			
Ext. 24v Wiring	✓	✓	✓	✓			
Single Burner							
External Gas	✓	✓	✓	✓			
Low Profile	✓	✓	✓	✓			
Efficiency	81	81	80	80			
<b>Competitor Z's Unit</b>	30	45	60	75			
Approved for Residential Use	✓	✓	✓	✓			
Full Load Amps (115 volt)	2.7	2.7	5.1	5.1			
Throw @ 10'	25	25	40	40			
Ext. 24v Wiring							
Single Burner							
External Gas							
Low Profile							
Efficiency	81	81	80	80			

Call your Reznor Rep to find a product that works for you 800-695-1901.

**REZNOR®**

Visit [reznorhvac.com](http://reznorhvac.com) for more information on the Reznor product line.

Reznor® and TCORE® are registered trademarks of Nortek Global HVAC, LLC. © Nortek Global HVAC, LLC 2021. All Rights Reserved.

660F-0521